

750II RANGE SELECTION GUIDE

Conductivity/TDS and Resistivity Monitor/controllers

CONDUCTIVITY/TDS

756II, 757II, 758II & 759II

Add Range NUMBER below to instrument model number, i.e. 758II-"112" = 0-50 ppm Digital Monitor/controller. Except as noted, Conductivity/TDS Monitor/controllers require a sensor with a cell constant of 1.0. The Model CS51 is the most commonly selected sensor due to its ease of use and low cost.

<u>RANGE</u>	<u>RANGE NUMBER</u>	<u>With ACCESSORY MODEL</u> <u>3RE or 3RO</u>
0-1 μ S *†	-101	
0-1 ppm *†	-102	
0-2 μ S *†	-103	
0-2 ppm *†	-104	
0-5 μ S *†	-105	
0-5 ppm *†	-106	
0-10 μ S †	-107	
0-10 ppm †	-108	
0-20 μ S	-109	0-20, 0-200, 0-2000 μ S
0-20 ppm	-110	0-20, 0-200, 0-2000 ppm
0-50 μ S	-111	0-50, 0-500, 0-5000 μ S
0-50 ppm	-112	0-50, 0-500, 0-5000 ppm
0-100 μ S	-113	0-100, 0-1000, 0-10,000 μ S
0-100 ppm	-114	0-100, 0-1000, 0-10,000 ppm
0-200 μ S	-115	0-200, 0-2000, 0-20,000 μ S
0-200 ppm	-116	0-200, 0-2000, 0-20,000 ppm
0-500 μ S	-117	0-500, 0-5000, 0-50,000 μ S **
0-500 ppm	-118	0-500, 0-5000, 0-50,000 ppm **
0-1000 μ S	-119	
0-1000 ppm	-120	
0-2000 μ S	-121	
0-2000 ppm	-122	
0-5000 μ S/0-5 mS ††	-123	
0-5000 ppm/0-5 ppt ††	-124	
0-10,000 μ S/0-10 mS ††	-125	
0-10,000 ppm/0-10 ppt ††	-126	
0-20,000 μ S/0-20 mS ††	-127	
0-20,000 ppm/0-20 ppt ††	-128	
0-50,000 μ S/0-50 mS **††	-129	
0-50,000 ppm/0-50 ppt **††	-130	
0-100 mS **††	-131	
0-100 ppt **††	-132	
0-200 mS **††	-133	
0-200 ppt **††	-134	

† Available in Digital models only.

†† Available with 4½ Digit Backlit LCD.

* CS51LC Conductivity Sensor (0.1 constant) required for these ranges

** CS52 Series Conductivity Sensor (10.0 constant) required for these ranges

Note: UNLESS ppm/NaCl is specified with order (ex. 758II-124N), ppm type conductivity instruments will be calibrated to the Myron L "442™" Natural Water Standard.

Custom and OEM Monitor/controllers available, contact us with your special needs.
Price and delivery upon request.

Resistivity Ranges listed on reverse.

MYRON L
COMPANY
Water Quality Instrumentation
Accuracy • Reliability • Simplicity

RESISTIVITY

751II, 752II, 753II & 754II

Add Range NUMBER below to instrument model number, i.e. 753II-"11" = 0-20 Megohms Digital Monitor/controller.

<u>RANGE</u>	<u>RANGE NUMBER</u>	<u>With ACCESSORY MODEL</u> <u>3RE or 3RO</u>
0-20 MΩ	-11	0-20 MΩ, 0-2 MΩ, 0-200 KΩ
0-10 MΩ †.....	-12	
0-5 MΩ †	-13	
0-2 MΩ	-14	
0-1 MΩ †.....	-15	
0-500 KΩ †.....	-16	
0-200 KΩ.....	-17	

† Available in digital models only.

Resistivity Monitor/controllers require a sensor with a cell constant of 0.05.
The Model CS10 is the most common selected due to its ease of use and low cost.

Custom and OEM Monitor/controllers available, contact us with your special needs. Price and delivery upon request.

TERMS AND CONDITIONS *(Additional information upon request)*

All special order items are non-returnable and non-refundable.
Minimum order \$25.00. All prices are US dollars and are F.O.B Carlsbad, CA.
Terms: 1% 10 days, net 30 days on approved credit.
Credit Cards accepted: Visa, MasterCard, and American Express
Because of our policy of continuous product improvement, the Myron L Company reserves the right to make changes in design, specifications, and prices without notice.

2450 Impala Drive
Carlsbad, CA 92010-7226 USA
Tel: 760-438-2021
Fax: 800-869-7668 / 760-931-9189
www.myronl.com

Built On Trust. Founded in 1957, the Myron L Company is one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

Water Quality Instrumentation
Accuracy • Reliability • Simplicity

